

Module	Specification
CPU	<ul style="list-style-type: none"> ● High performance ARM CPU ● Equipped with financial security chip
Memory	<ul style="list-style-type: none"> ● Mass storage
Display	<ul style="list-style-type: none"> ● Resolution :320*240 ● Visual area size: 48.96(W) x 36.72(H)
Customer display	<ul style="list-style-type: none"> ● Support
Keyboard	<ul style="list-style-type: none"> ● Support
Camera	<ul style="list-style-type: none"> ● 300,000 pixels
Contactless card reader (Optional)	<ul style="list-style-type: none"> ● (Optional) Support, 13.56MHz, ISO 14443A&B / Mifare standards;
Electronic signature (Optional)	<ul style="list-style-type: none"> ● (Optional) Resistive touch screen
Password keyboard (Optional)	<ul style="list-style-type: none"> ● Support ANSI X9.8/ISO9564, ANSI X9.9/ISO8731 ● Support DES, 3DES, RSA, SHA-256 ● Support MK/SK, FIXEDKEY, DUKPT
Communication	<ul style="list-style-type: none"> ● GPRS: Support; ● USB/ Serial port: Support ● WIFI (Optional) : Support;
Power adapter (Optional)	<ul style="list-style-type: none"> ● DC 5V, 1.0A
battery	<ul style="list-style-type: none"> ● Large capacity lithium battery
Indicator light	<ul style="list-style-type: none"> ● Support
Audio	<ul style="list-style-type: none"> ● Support
Dimension	<ul style="list-style-type: none"> ● 172.5(L)*78.5(W)*40.7(H) mm
Work environment	<ul style="list-style-type: none"> ● Operating Temperature: -10°C~50°C ● Storage Temperature: -20°C~70°C ● Humidity: 10%~95% non-condensing